IEEE HOME | SEARCH IEEE | SHOP | WEB ACCOUNT | CONTACT IEEE



Membership Publicat	ions/Services Standards Conferences Careers/Jobs
	RELEASE 17
Help FAQ Terms IEEE	Peer Review Quick Links Sea
Welcome to IEEE Xplare* O Home What Can I Access?	Your search matched 2 of 1043368 documents. A maximum of 500 results are displayed, 15 to a page, sorted by Relevance Descending order.
O- Log-out	Refine This Search:
Tables of Contents	You may refine your search by editing the current search expression or enterinew one in the text box.
O- Journals & Magazines	controller area network <and>module<and>storage Search</and></and>
O- Conference Proceedings	☐ Check to search within this result set
O- Standards	Results Key: JNL = Journal or Magazine CNF = Conference STD = Standard
Search	
O- By Author O- Basic O- Advanced	1 Embedded controllers, field bus and a modular I/O concept: central elements of BESSY II controls Bergl, J.; Kuner, B.; Lange, R.; Muller, I.; Muller, R.; Pfeiffer, G.; Rahn, J.; Rudiger, H.;
Member Services	Particle Accelerator Conference, 1997. Proceedings of the 1997, Volume: 2,
O- Join IEEE O- Establish IEEE	May 1997 Pages:2493 - 2495 vol.2
Web Account	[Abstract] [PDF Full-Text (484 KB)] IEEE CNF
O- Access the IEEE Member Digital Library	2 Autonomous deep-ocean lander vehicles; modular approaches to de and operation Priede, I.G.; Addison, S.; Bradley, S.; Bagley, P.M.; Gray, P.; Yau, C.; Rolin,
Print Format	Blandin, J.; Legrand, J.; Cremer, A.; Witte, U.; Pfannkuche, O.; Tengberg, A. Hulth, S.; Helder, W.; Van Weering, T.; OCEANS '98 Conference Proceedings, Volume: 3, 28 Sept1 Oct. 1998

[Abstract] [PDF Full-Text (688 KB)] IEEE CNF

Pages:1238 - 1244 vol.3

Home | Log-out | Journals | Conference Proceedings | Standards | Search by Author | Basic Search | Advanced Search | Join IEEE | Web Account |
New this week | OPAC Linking Information | Your Feedback | Technical Support | Email Alerting | No Robots Please | Release Notes | IEEE Online
Publications | Help | FAQ | Terms | Back to Top

Copyright © 2004 IEEE — All rights reserved

BEST AVAILABLE COPY

IEEE HOME | SEARCH IEEE | SHOP | WEB ACCOUNT | CONTACT IEEE



Membership Publica	ations/Services Standards Conferences Careers/Jobs
JEEE	Welcome United States Patent and Trademark Office
Help FAQ Terms IEE	E Peer Review Quick Links Sea
Welcome to IEEE <i>Xplore*</i> — Home — What Gan I Access?	Your search matched 0 of 1043368 documents. A maximum of 500 results are displayed, 15 to a page, sorted by Relevance Descending order.
O- Log-out	Refine This Search:
Tables of Cantenis	You may refine your search by editing the current search expression or enterinew one in the text box.
O- Journals & Magazines	controller area network <and>module<and>multiplexer</and></and>
O- Conference Proceedings	☐ Check to search within this result set
O- Standards	Results Key: JNL = Journal or Magazine CNF = Conference STD = Standard
Search	
O- By Author	
O- Basic	Results:
O- Advanced	No documents matched your query.
Member Services	
O- Join IEEE O- Establish IEEE Web Account	
O- Access the IEEE Member	

Print Format

Digital Library

Home | Log-out | Journals | Conference Proceedings | Standards | Search by Author | Basic Search | Advanced Search | Join IEEE | Web Account |
New this week | OPAC Linking Information | Your Feedback | Technical Support | Email Alerting | No Robots Please | Release Notes | IEEE Online
Publications | Help | FAQ | Terms | Back to Top

Copyright © 2004 IEEE — All rights reserved

BEST AVAILABLE COPY

x n x previo x conten

Next: Sensor Module Up: Modules Previous: Modules

Controller Module

The Controller Module is based on a commercially available universal microcontroller module (Microkey 20CN592, [3]) designed around the Philips 80C592 8-bit microcontroller [2] running at a clock frequency of 16 MHz.

The microcontroller has an integrated CAN controller and the on-board CAN transceiver (Philips 82C250) provides an ISO/DIS-11898 standard CAN-bus interface.

The module offers 48 kByte of user application ROM (flash) and 63.5 kByte of RAM. This amount of memory is enough to build quite large applications. User application code can be downloaded through a serial port (standard) or optionally via the CAN-bus (a future option which could be very useful once the modules are integrated into an experiment); these features are provided by the onboard firmware delivered with the module.

The Controller Module also contains a multiplexer chip to enable connections to several Sensor Modules. One Controller Module may control up to about 16 Sensor Modules (NB: up to 8 in the current hardware/software implementation); a digital multiplexer-chip is used to switch the controller's serial interface I/O port to any of the connected Sensor Modules.

BEST AVAILABLE COPY